

SUBMITTAL DATA - INDOOR UNIT VE1C024N432U VRF 1-WAY CASSETTE TYPE EVAPORATOR

Job Name:	Engineer:
Location:	Architect:
Schedule No.:	Date:
System Designation:	For: Reference Approval Review Construction

FEATURES

- · Auto Addressing installation
- Auto Restart
- Integrated Condensate Pump
- Built-in Electronic Expansion Valve
- LED Display
- Replaceable Front Panel

- · Washable Filter
- Anti-Freezing Protection
- Water Overflow Protection


PRODUCT WARRANTY

All covered components - Five year limited warranty

SPECIFICATIONS PERFORMANCE		
Cooling Capacity* (Btu/h) Heating Capacity* (Btu/h) Airflow (CFM)	High Medium Low	24,230 27,300 589 400 353
Sound Pressure Level (dBA)	H/M/L	44/39/36
Power Supply (V / Hz / Ph) MOP (A) Rated Current (A)	220-240/50/1 - 208 Cooling Heating	3-230/60/1 6 0.86 0.86

- Unit Dimensions (in) Height 7 7/8
 Width 47 1/4
 Depth 18 1/2
- Liquid Pipe Connection (in)3/8Gas Pipe Connection (in)5/8Shipping Weight (lb)64.5Net Weight (lb)57.4





- 1. Pipe Connection
- 2. Front Panel
- 3. Air Louver
- 4. Swing Louvers
- 5. Air Grill
- 6. Air Filter
- 7. Main Body
- 8. Built-in Condensate Pump
- 9. Drain Pipe

NOTES:

DIMENSIONS

*Cooling and Heating Capacity data is rated at the following conditions:

Cooling: 80 °F DB / 67 °F WB Indoor, 95 °F DB Outdoor

Heating: 70 °F DB Indoor, 47 °F DB

NOTE – Due to Lennox' ongoing commitment to quality, Specifications, Ratings and Dimensions subject to change without notice and without incurring liability. Improper installation, adjustment, alteration, service or maintenance can cause property damage or personal injury. Installation and service must be performed by a qualified installer and servicing agency. ©2024 Lennox Industries Inc.



SUBMITTAL DATA - INDOOR UNIT VE1C024N432U VRF 1-WAY CASSETTE TYPE EVAPORATOR

DIMENSIONAL DRAWINGS

TOP VIEW



Side	mm	in	Description
Α	1350	53 1/7	Front Panel Width
В	1300	51 1/6	Ceiling Outlet Width
С	1246	49	Holding Brackets Width
W	1200	47 1/4	Width
E	356	14	Holding Brackets Depth
D	470	18 1/2	Depth
F	510	20	Ceiling Outlet Depth
G	555	21 6/7	Front Panel Depth

NOTE – Due to Lennox' ongoing commitment to quality, Specifications, Ratings and Dimensions subject to change without notice and without incurring liability. Improper installation, adjustment, alteration, service or maintenance can cause property damage or personal injury. Installation and service must be performed by a qualified installer and servicing agency. ©2024 Lennox Industries Inc.