



SUBMITTAL DATA - OUTDOOR UNIT

VEP096N432K2

VRF 2nd GEN HIGH EFFICIENCY HEAT PUMP

Job Name:

Location:

Schedule No.:

System Designation:

Engineer:

Architect:

Date:

For: ___ Reference ___ Approval ___ Review ___ Construction

FEATURES

- Two-pipe heat pump
- Accelerated complete coil defrost
- Hermetically sealed compressor with crankcase heater
- Thermal and Current protection in Compressor
- Steel casing with baked enameled finish Compressor
- Access to electrical box for ease of maintenance
- High efficiency DC Inverter Scroll compressor
- Compressor mounted on vibration isolation pads
- Subcooling Control Technology
- Plastic Fan Blade
- Intelligent duty cycle operation
- Hydrophilic Aluminum Gold Fin
- No oil balance pipe needed

PRODUCT WARRANTY

Compressor - Seven year limited warranty

All other components - Five year limited warranty

SPECIFICATIONS

PERFORMANCE

Cooling Capacity* (Btu/h)		95,480
EER (W/W)		5.11
IEER (Btu/W)	Ducted	25.74
	Non ducted	26.50
Cooling Power Input (W)		5,480
Heating Capacity* (Btu/h)		107,482
COP (W/W)		5.25
Heating Power Input (W)		6,000

ELECTRICAL DATA

Power Supply	220-240V/3Ph/50Hz - 208-230V/3Ph/60Hz
MOCP (A)	40
MCA (A)	38.8
No. of Compressors	1
No. of Fans	1

GENERAL DATA

Combination Ratio Indoor / Outdoor	50% to 135%
Max. # of Indoor Units	16 units
Sound Pressure Level (dBA)	59
Refrigerant Type	R410a
Factory Refrigerant Charge (lbs / kg)	12.13 / 5.5

DIMENSIONS

Unit Dimensions (in)	Height	66 1/2
	Width	36 5/8
	Depth	30 1/2
Liquid Pipe Connection (in)		3/8
Gas Pipe Connection (in)		7/8

Shipping Weight (lb / kg)	529 / 240
Net Weight (lb)	507 / 230

NOTES:

*Cooling and Heating Capacity data is rated at the following conditions:

Cooling: 80 °F DB / 67 °F WB Indoor; 95 °F DB / 75 °F WB Outdoor

Heating: 70 °F DB, 70 °F WB Indoor; 47 °F DB, 43 °F WB Outdoor

NOTE – Due to Lennox' ongoing commitment to quality, Specifications, Ratings and Dimensions subject to change without notice and without incurring liability. Improper installation, adjustment, alteration, service or maintenance can cause property damage or personal injury. Installation and service must be performed by a qualified installer and servicing agency. ©2023 Lennox Industries Inc.






SUBMITTAL DATA - OUTDOOR UNIT

VEP096N432K2

VRF 2nd GEN HIGH EFFICIENCY HEAT PUMP

DIMENSIONAL DRAWINGS

Unit: mm(inch)



NOTE – Due to Lennox' ongoing commitment to quality, Specifications, Ratings and Dimensions subject to change without notice and without incurring liability. Improper installation, adjustment, alteration, service or maintenance can cause property damage or personal injury. Installation and service must be performed by a qualified installer and servicing agency. ©2023 Lennox Industries Inc.