# SUBMITTAL DATA – CASSETTE TYPE
# LISH024160U332 - LICH8024160U332
# SINGLE ZONE INVERTER MINI-SPLIT HEAT PUMP

| | |
|---|---|
| Job: | Engineer: |
| Location: | Architect: |
| Schedule No.: | Date: |
| System Designation: | |

## FEATURES

Outdoor Unit: **LISH024160U332**
Outdoor Unit Cat Number: **37H78**



- DC Inverter Compressor
- DC ODU Motor
- DC Electronic Expansion Valve(EXV)

Indoor Unit: **LICH8024160U332**
Indoor Unit Cat Number: **37J09**



- Auto Restart
- 360° Airflow
- DC IDU Motor
- Washable Filter
- Built-in electric box

## PIPING

| Line Set and Elevation Guidelines | |
|---|---|
| Maximum Line Set Length ft. (m) | 98.4 ft. (30 m) |
| Maximum Elevation - Outdoor Unit Below/Above Indoor Unit ft. (m) | 65.6 ft. (20 m) |
| Liquid Line Set Diameter (in.) | 3/8'' |
| Gas Line Set Diameter (in.) | 5/8'' |

## PRODUCT WARRANTY

5 Year Limited Warranty*

## OPTIONAL ACCESORIES

WIFI Wired Control (37J42 LCACWIFI1-1332 )

**NOTE** – Due to Lennox' ongoing commitment to quality, Specifications, Ratings, and Dimensions are subject to change without notice and without incurring liability. Improper installation, adjustment, alteration, service or maintenance can cause property damage or personal injury. Installation and service must be performed by a qualified installer and servicing agency

495616 (202407) ©2024 Lennox Industries, Inc.

# SUBMITTAL DATA – CASSETTE TYPE
# LISH024160U332 - LICH8024160U332
# SINGLE ZONE INVERTER MINI-SPLIT HEAT PUMP

## OUTDOOR SPECIFICATIONS

| PERFORMANCE | |
|---|---|
| Cooling Capacity (Btu/h) | 24,200 |
| EER(W/W) | 3.23 |
| SEER(BTUH/W) | 16 |
| Heating Capacity (Btu/h) | 27,200 |
| HSPF | 8 |

| | |
|---|---|
| Outdoor Fan Total Air Volume (CFM) | 2,119 |
| Ambient Temperature Operating Range | |
| Cooling | 5°F(-15°C) - 118°F(48°C) |
| Heating | 5°F(-15°C) - 75°F(24°C) |

| ELECTRICAL DATA | |
|---|---|
| Power Supply (V/Hz/ϕ) | 220-240-50/60-1 |
| Rated Current (A) | 12.5 |
| Minimum Circuit Ampacity (A) | - |
| Maximum Overcurrent Protection (A) | - |
| Compressor RLA (A) | 6.06 |
| No. of Compressors | 1 |


| GENERAL DATA | |
|---|---|
| Connection Ratio (%) | 100% |
| Max. # of Indoor Units | 1 |
| Sound Data (dBA) - Cooling/Heating | 58 |
| Refrigerant type | R32 |
| Factory refrigerant charge | 2.43 lbs. 38.8 oz. |

| DIMENSIONS | | |
|---|---|---|
| Unit Dimensions (in) | Height | 26.0 |
| | Width | 35.0 |
| | Depth | 13.4 |
| Shipping Weight (lb) | | 97.0 |
| Net Weight (lb) | | 88.2 |

**NOTES**

1. Cooling and Heating Capacity data is rated at the following conditions:
Cooling: 80°FDB / 67°FWB Indoor, 95°FDB/ 75°FWB Outdoor
Heating: 68°FDB / 59°FWB Indoor, 45°FDB/ 43°FWB

## OUTDOOR DIMENSIONAL DRAWINGS - INCHES (MM)




| ODU | UNIT | A | B | C | D | E | F | G |
|---|---|---|---|---|---|---|---|---|
| 24K/34K | mm | 985 | 402 | 660 | 570 | 371 | 889 | 340 |
| | inch | 38.78 | 15.83 | 25.98 | 22.44 | 14.61 | 35.00 | 13.39 |

**NOTE** – Due to Lennox' ongoing commitment to quality, Specifications, Ratings, and Dimensions are subject to change without notice and without incurring liability. Improper installation, adjustment, alteration, service or maintenance can cause property damage or personal injury. Installation and service must be performed by a qualified installer and servicing agency

495616 (202407) ©2024 Lennox Industries, Inc.

# SUBMITTAL DATA – CASSETTE TYPE
# LISH024160U332 - LICH8024160U332
# SINGLE ZONE INVERTER MINI-SPLIT HEAT PUMP

## INDOOR SPECIFICATIONS

| PERFORMANCE | | |
|---|---|---|
| Airflow (CFM) | Turbo | 765 |
| | High | 706 |
| | Medium | 647 |
| | Low | 530 |
| External Static Pressure (in. w.g.) | | - |
| Sound Pressure (dBA) | Turbo | 44 |
| | High | 43 |
| | Medium | 41 |
| | Low | 38 |
| **ELECTRICAL DATA** | | |
| Power Supply (V/Hz/ϕ) | | 220-240-50/60-1 |
| Full load amps (FLA) | | - |
| Power Output (W) | | - |
| **DIMENSIONS** | | |
| Unit Dimensions (in) | Height | 7.9 |
| | Width | 33.1 |
| | Depth | 33.1 |
| Unit Net/Shipping Weight (lb) | | 46.3/59.5 |


## WIRELESS REMOTE CONTROLLER SPECIFICATION

| 37B67 (YAP1F7) | |
|---|---|
| Power Supply | 2 AAA Batteries (Included) |
| Setpoint Range | 61°F(16ºC ) - 86°F(30ºC ) |
| Effective Receiving Range | 26 ft.(8m) |

## DISPLAY



## INDOOR DIMENSIONAL DRAWINGS - INCHES (MM)




| IDU | UNIT | A | B | C | D | E | F | G |
|---|---|---|---|---|---|---|---|---|
| 24K | mm | 950 | 890 | 840 | 680 | 780 | 200 | 135 |
| | inch | 37.4 | 35 | 33.1 | 26.8 | 30.7 | 7.9 | 5.3 |

**NOTE** – Due to Lennox' ongoing commitment to quality, Specifications, Ratings, and Dimensions are subject to change without notice and without incurring liability. Improper installation, adjustment, alteration, service or maintenance can cause property damage or personal injury. Installation and service must be performed by a qualified installer and servicing agency

495616 (202407) ©2024 Lennox Industries, Inc.