



SUBMITTAL DATA – FLOOR CEILING TYPE
LISH034160U332 - LIUH034160U332
SINGLE ZONE INVERTER MINI-SPLIT HEAT PUMP

Job: _____
Location: _____
Schedule No.: _____
System Designation: _____

Engineer: _____
Architect: _____
Date: _____


FEATURES

Outdoor Unit: **LISH034160U332**
Outdoor Unit Cat Number: **37H81**



- DC Inverter Compressor
- DC ODU Motor
- DC Electronic Expansion Valve(EXV)

Indoor Unit: **LIUH034160U332**
Indoor Unit Cat Number: **37J22**



- Auto Restart
- Double Louver
- DC IDU Motor
- Washable Filter

PIPING

Line Set and Elevation Guidelines

Maximum Line Set Length ft. (m)	98.4 ft. (30 m)
Maximum Elevation - Outdoor Unit Below/Above Indoor Unit ft. (m)	82 ft. (25 m)
Liquid Line Set Diameter (in.)	3/8"
Gas Line Set Diameter (in.)	5/8"

PRODUCT WARRANTY

5 Year Limited Warranty*

OPTIONAL ACCESORIES

WIFI Wired Control (37J42 LCACWIFI1-1332)

NOTE – Due to Lennox' ongoing commitment to quality, Specifications, Ratings, and Dimensions are subject to change without notice and without incurring liability. Improper installation, adjustment, alteration, service or maintenance can cause property damage or personal injury. Installation and service must be performed by a qualified installer and servicing agency



SUBMITTAL DATA – FLOOR CEILING TYPE
LISH034160U332 - LIUH034160U332
SINGLE ZONE INVERTER MINI-SPLIT HEAT PUMP

OUTDOOR SPECIFICATIONS

PERFORMANCE

Cooling Capacity (Btu/h)	34,100
EER(W/W)	3.21
SEER(BTUH/W)	16
Heating Capacity (Btu/h)	37,500
HSPF	8

Outdoor Fan Total Air Volume (CFM)	2,119
Ambient Temperature Operating Range	
Cooling	5°F(-15°C) - 118°F(48°C)
Heating	5°F(-15°C) - 75°F(24°C)

ELECTRICAL DATA

Power Supply (V/Hz/ϕ)	220-240-50/60-1
Rated Current (A)	15.5
Minimum Circuit Ampacity (A)	-
Maximum Overcurrent Protection (A)	-
Compressor RLA (A)	4.3
No. of Compressors	1

GENERAL DATA

Connection Ratio (%)	100%
Max. # of Indoor Units	1
Sound Data (dBA) - Cooling/Heating	58
Refrigerant type	R32
Factory refrigerant charge	3.3 lbs. 52.9 oz.


DIMENSIONS

Unit Dimensions (in)	Height	26
	Width	35
	Depth	13.4
Shipping Weight (lb)		112.5
Net Weight (lb)		103.6

NOTES

1. Cooling and Heating Capacity data is rated at the following conditions:
Cooling: 80°FDB / 67°FWB Indoor, 95°FDB/ 75°FWB Outdoor
Heating: 68°FDB / 59°FWB Indoor, 45°FDB/ 43°FWB

OUTDOOR DIMENSIONAL DRAWINGS - INCHES (MM)



ODU	UNIT	A	B	C	D	E	F	G
24K/34K	mm	985	402	660	570	371	889	340
	inch	38.78	15.83	25.98	22.44	14.61	35.00	13.39

NOTE – Due to Lennox' ongoing commitment to quality, Specifications, Ratings, and Dimensions are subject to change without notice and without incurring liability. Improper installation, adjustment, alteration, service or maintenance can cause property damage or personal injury. Installation and service must be performed by a qualified installer and servicing agency



SUBMITTAL DATA – FLOOR CEILING TYPE
LISH034160U332 - LIUH034160U332
SINGLE ZONE INVERTER MINI-SPLIT HEAT PUMP

INDOOR SPECIFICATIONS

PERFORMANCE

Airflow (CFM)	Turbo	1059
	High	942
	Medium	824
	Low	706
External Static Pressure (in. w.g.)		-
Sound Pressure (dBA)	Turbo	49
	High	47
	Medium	44
	Low	42

ELECTRICAL DATA

Power Supply (V/Hz/φ)	220-240-50/60-1
Full load amps (FLA)	-
Power Output (W)	*

DIMENSIONS

Unit Dimensions (in)	Height	9.3
	Width	47.2
	Depth	26.2
Unit Net/Shipping Weight (lb)		70.6/81.6

WIRELESS REMOTE CONTROLLER SPECIFICATION

37B67 (YAP1F7)

Power Supply	2 AAA Batteries (Included)
--------------	-------------------------------


Setpoint Range	61°F(16°C) - 86°F(30°C)
----------------	-------------------------

Effective Receiving Range	26 ft.(8m)
---------------------------	------------

DISPLAY



INDOOR DIMENSIONAL DRAWINGS - INCHES (MM)



IDU	UNIT	A	B	C	D	E
34K	mm	1200	235	1142	280	665
	inch	47.24	9.25	44.96	11.02	26.18

NOTE – Due to Lennox' ongoing commitment to quality, Specifications, Ratings, and Dimensions are subject to change without notice and without incurring liability. Improper installation, adjustment, alteration, service or maintenance can cause property damage or personal injury. Installation and service must be performed by a qualified installer and servicing agency