



SUBMITTAL DATA - OUTDOOR UNIT VEP075N432G2

VRF 2nd GEN HIGH EFFICIENCY HEAT PUMP

Job Name: _____
Location: _____
Schedule No.: _____
System Designation: _____

Engineer: _____
Architect: _____
Date: _____
For: _____ Reference _____ Approval _____ Review _____ Construction

FEATURES

- Two-pipe heat pump
- Accelerated complete coil defrost
- Hermetically sealed compressor with crankcase heater
- Thermal and Current protection in Compressor
- Steel casing with baked enameled finish Compressor
- Access to electrical box for ease of maintenance
- High efficiency DC Inverter Scroll compressor
- Intelligent duty cycle operation
- Hydrophilic Aluminum Gold Fin
- Compressor mounted on vibration isolation pads
- Subcooling Control Technology
- Plastic Fan Blade
- No oil balance pipe needed

PRODUCT WARRANTY

Compressor - Seven year limited warranty
All other components - Five year limited warranty

SPECIFICATIONS

PERFORMANCE

Cooling Capacity* (Btu/h)		76,432
EER (W/W)		5.25
IEER (Btu/W)	Ducted	27.73
	Non ducted	28.60
Cooling Power Input (W)		4,270
Heating Capacity* (Btu/h)		85,304
COP (W/W)		5.68
Heating Power Input (W)		4,400

ELECTRICAL DATA

Power Supply (V / Ph / Hz)	440-460/3/60
MOCP (A)	25
MCA (A)	19.6
No. of Compressors	1
No. of Fans	1

GENERAL DATA

Combination Ratio Indoor / Outdoor	50% to 135%
Max. # of Indoor Units	13 units
Sound Pressure Level (dBA)	58
Refrigerant Type	R410a
Factory Refrigerant Charge (lbs / kg)	12.13 / 5.5

DIMENSIONS

Unit Dimensions (in)	Height	66 1/2
	Width	36 1/2
	Depth	30 1/2
Liquid Pipe Connection (in)		3/8
Gas Pipe Connection (in)		3/4
Shipping Weight (lb / kg)		529 / 240
Net Weight (lb/kg)		507 / 230

NOTES:

*Cooling and Heating Capacity data is rated at the following conditions:

Cooling: 80 °F DB / 67 °F WB Indoor; 95 °F DB / 75 °F WB Outdoor

Heating: 70 °F DB, 70 °F WB Indoor; 47 °F DB, 43 °F WB Outdoor

NOTE – Due to Lennox' ongoing commitment to quality, Specifications, Ratings and Dimensions subject to change without notice and without incurring liability. Improper installation, adjustment, alteration, service or maintenance can cause property damage or personal injury. Installation and service must be performed by a qualified installer and servicing agency. ©2022 Lennox Industries Inc.






SUBMITTAL DATA - OUTDOOR UNIT

VEP075N432G2

VRF 2nd GEN HIGH EFFICIENCY HEAT PUMP

DIMENSIONAL DRAWINGS

Unit: mm(inch)



NOTE – Due to Lennox' ongoing commitment to quality, Specifications, Ratings and Dimensions subject to change without notice and without incurring liability. Improper installation, adjustment, alteration, service or maintenance can cause property damage or personal injury. Installation and service must be performed by a qualified installer and servicing agency. ©2022 Lennox Industries Inc.

Submittal Rev-A-0823